

**D4 SERIES
SPDT SWITCH
DC-12.4 GHz ◆ N, BNC, TNC**

**Click Here to
Request Quote**



The **D4 Series** features N, BNC or TNC connectors and a frequency range of DC to 12.4 GHz.

This series is available with fail-safe, latching self cut-off or pulse latching functions.

RF Impedance:	50 ohms nominal
Temperature Range:	-35°C to +85°C ambient
Operating Life:	1,000,000 cycles min.
Switching Time:	15 mSec max.
Switching Sequence:	Break Before Make
Environmental:	Designed in Accordance to MIL-DTL-3928 (Testing and Operation Modes)

SPECIFICATIONS

Frequency	VSWR (max.)	Insertion Loss (dB max.)	Isolation (dB min.)
DC-3 GHz	1.20	0.20	80
3-8 GHz	1.35	0.35	70
8-12.4 GHz	1.50	0.50	60

Actuator Current (typical)	12Vdc	15 Vdc	24 Vdc	28Vdc
Fail-safe	240mA	240mA	170mA	190mA
Latching	140mA	140mA	130mA	130mA

* If reduced coil current is required, please contact Factory.

AVAILABLE OPTIONS

OPTION 2 RF CONNECTORS	OPTION 4 VOLTAGE	OPTION 5 ACTUATOR	OPTION 6 FREQUENCY	OPTION 8 SPECIAL OPTIONS
1 - N 2 - BNC 3 - TNC	1 - 6 Vdc +/- 10% 2 - 12 Vdc +/- 10% 3 - 24-30 Vdc 4 - 48 Vdc +/- 10% 5 - 110 Vac +/- 10% 6 - 12-15 Vdc 7 - 18-20 Vdc 8 - 20-24 Vdc	Fail-safe A - Standard B - Indicators M - Diodes Q - Diodes, Indicators Latching Self Cut-Off D - Diodes E - Diodes, Indicators Pulse Latching C - Standard F - Indicators Y - Diodes L - Diodes, Indicators Normally Open K - Standard H - Indicators J - Diodes G - Diodes, Indicators	2 - DC to 12.4 GHz	L - TTL (High) LL - TTL (Low) P - High Power Handling
OPTION 3 TERMINALS			OPTION 7 POLARITY	
1 - Solder Terminals 2 - Circular Connector 4 - Sub M iniature D-Shell Connector			0 - Not Applicable 8 - Positive Common 9 - Negative Common	

D4

-

2

Option 1
Series

Option 2
RF Connectors

Option 3
Terminals

Option 4
Voltage

Option 5
Actuator

Option 6
Frequency

Option 7
Polarity

Option 8
Special
Options

DC TERMINAL FUNCTION

PIN	FAILSAFE							LATCHING							NORMALLY OPEN					
	A	M	A, M w/ TTL	B	Q	B, Q w/ TTL	C, Y	C, Y w/ TTL	D	D w/ TTL	E	E w/ TTL	F, L	F, L w/ TTL	J	K	J, K w/ TTL	G	H	G, H w/ TTL
1	1	+1	+A	COM	COM	COM	COM+/-	+A	COM+/-	+A	COM	COM	COM	COM	COM+/-	C	+A	COM	COM	2
2	N/A	N/A	N/A	1	1	1	N/A	-B	N/A	-B	1	1	1	1	N/A	N/A	-B	1	1	1
3	N/A	N/A	N/A	2	2	2	N/A	N/A	N/A	N/A	2	2	2	2	N/A	N/A	N/A	2	2	COM
4	2	-2	-B	1	+1	+A	1-/+	1	1-/+	1	COM+/-	+A	COM+/-	+A	1-/+	1	1	COM+/-	COM	+A
5	N/A	N/A	2	2	-2	-B	2-/+	2	2-/+	2	1-/+	-B	1-/+	-B	2-/+	2	2	1-/+	1	-B
6	N/A	N/A	N/A	N/A	N/A	2	N/A	N/A	N/A	N/A	2-/+	1	2-/+	1	N/A	N/A	N/A	2-/+	2	1
7	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2	N/A	2	N/A	N/A	N/A	N/A	N/A	2

SCHEMATICS


Pages 139-143

FIG.	1	1	2	1	1	2	15	16	9	10	9	10	15	16	21	21	22	21	21	22
------	---	---	---	---	---	---	----	----	---	----	---	----	----	----	----	----	----	----	----	----

OUTLINE DRAWING DIMENSION "A"

1.85"	1.85"	1.85"	1.85"	1.85"	1.85"	1.85"	1.85"	2.10"	1.85"	2.10"	1.85"	2.10"	1.85"	2.10"	1.85"	1.85"	2.10"	1.85"	1.85"	2.10"
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

SIDE VIEW



FRONT VIEW

